




DAVINCI TECHNICAL DATA GUIDE

SINGLE DISC CHECK VALVES

WAFER TYPE

Ref. 1611A-KIQ / PN 40



Application

Water supply and pumping systems.
Backflow prevention in industrial pipelines.
HVAC and cooling-water circuits.
Oil, gas and compressed-air services.
Chemical and mildly corrosive-fluid lines.

Approvals/Standards

Design and manufacture according to GB/T 12235.
Pressure Tests acc. to EN 12266-1 Rate A. GB/T13927-1992
Pressure Tests: Seat: 1,1 x PN.

Certifications

CE

Range

DN15-200, PN40





GENERAL CHARACTERISTICS

Sizes DN15 to DN200.

Mounting between PN10, PN16, PN25 and PN40 flanges.

WORKING CONDITIONS


Pressure ratings: Up to 4.0 Mpa.

Working temperature: -40°C + 180°C.

Suitable media: water, oil, gas and compatible mildly corrosive fluids.

Nº	ITEM	MATERIAL
1	Valve plate	CF8M
2	Body	CF8M
3	Spring washer	CF8M
4	Stem	CF8M

Components may be replaced with materials of equivalent or superior grade without prior notice, in accordance with our continuous improvement policy.



DN	L	B	H	Weight (kg)
15	50	19	29	0.19
20	55	17	30	0.27
25	69	25	29	0.37
32	79	30	32	0.59
40	89	38	35	0.81
50	104	50	40	1
65	122	60	50	1.54
80	138	78	60	2.3
100	159	94	70	3.5
125	190	119	81	7.1
150	212	140	102	10.2
200	267	191	112	12.3



CONTACT US

DAVINCI VALVES ORDER REQUEST

Ref. 1611A-KIQ / PN 40



Head Office CHENGDU

Room 3208 Unit 1 Building 1,
No. 6 Zhiquan Section, Dongda Street
Jinjiang District, Chengdu, Sichuan
CHINA

+86 17340168233 +86 19302892712
valves@davincivalves.com

Europe Office MADRID
SPAIN
zuzana@davincivalves.com

WEBSITE

davincivalves.com



YOUR QUALITY WATER PROJECTS PARTNER
For professionals who look for more.